

Product Description

Rubber Cable

Product Name	Rubber Cable
Coductor	Copper / Aluminum, based on client's requirements
Construction	Bare copper wire
	Insulation jacket
	PVC sheath
Colors	Assorted upon request
Voltage	300/500V 450/750V
Application	These cables are used for lightweight hand and workshop tool while the other groups are suitable for increasingly higher levels of stress and heavy duty equipment.
Specifications	CCC ISO certificated
	Strict QC
	Prompt delivery
OEM/ODM	Available
Sample	Free, freight charge prepaid or negotiation
Payment Term	T/T, L/C
MOQ	100 Kilometer/Kilometers
Port Of Loading	Ningbo
Delivery Detail	10days after confirming the order

Characteristics

Normal area (mm2)	Structure (mm)	Insulated thickness (mm)	Approx dia. (mm)	Normal area (mm2)	Structure (mm)	Insulated thickness (mm)	Approx dia. (mm)
2x0.75	24/0.20	0.60	7.50	4x2.5	49/0.25	0.90	12.50
2x1.0	32/0.20	0.60	7.80	4x4.0	56/0.30	1.00	14.80
2x1.5	30/0.25	0.80	9.20	4x6.0	84/0.30	1.00	16.50
2x2.5	49/0.25	0.90	11.00	4x10.0	84/0.40	1.20	22.70
2x4.0	56/0.28	1.00	12.50	4x16.0	126/0.40	1.20	25.80
3x1.0	32/0.20	0.60	8.00	4x25.0	196/0.40	1.40	33.50
3x1.5	30/0.25	0.80	9.20	4x35.0	276/0.40	1.40	37.50
3x2.5	49/0.25	0.90	11.50	4x50.0	396/0.40	1.60	43.00
3x4.0	56/0.30	1.00	13.30	5x2.5	49/0.25	0.90	14.00
3x6.0	84/0.30	1.00	15.00	5x4.0	56/0.30	1.00	16.60
3x10.0	84/0.40	1.20	22.80	5x6.0	84/0.30	1.00	18.50
3x16.0	126/0.40	1.20	26.0	5x10.0	84/0.40	1.20	27.00
3x25.0	196/0.40	1.40	30.00	5x16.0	126/0.40	1.20	31.00
3x35.0	276/0.40	1.40	33.80	5x25.0	196/0.40	1.40	37.00
3x50.0	396/0.40	1.60	39.00	5x35.0	276/0.40	1.40	42.50
4x1.5	30/0.25	0.80	11.00	5x50.0	396/0.40	1.60	48.00